



Specifications Ledvance LED SPOT FIRE RATED Aluminium 8W 680lm 36D - 930 Warm White | Cutout 68mm - IP65 - Best Colour Rendering - Dimmable

[View Product](#)

General Information

| | |
|--------------------------|--|
| SKU | 247091 |
| EAN | 4058075799745 |
| Brand | Ledvance |
| Manufacturer Name | SP FP FIX P 8W 930 PS DIM IP65 WT LEDV |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 50000 |

Technical Information

| | |
|-----------------------------|-----------------|
| Technology | LED Integrated |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable |
| Colour Code | 930 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 90-99 |
| Colour of Light | White |
| Light colour options | Single Color |
| Luminous Efficacy (lm/W) | 85 |
| Beam Angle (degree) | 36 |
| Product Type Category | LED spotlight |

Fixture Information

| | |
|----------------|-----|
| Including bulb | Yes |
|----------------|-----|

| | |
|------------------------|--------------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 68 |
| Optical Cover | PMMA (Polymethyl methacrylate) |
| IP-rating | IP65 |
| Impact Protection (IK) | IK05 - 0.70 joule |
| Operating Temperature | -20 to +40 |
| Housing | Aluminium |
| Colour of material | White |
| Colour of the Fixture | White |
| Power factor | >0.90 |
| Tiltable | No |
| Fixture Connection | PI [Push-in connector 2-pole] |
| Series | SPOT FIRE RATED |

Dimensions

| | |
|---------------|----|
| Length (mm) | 81 |
| Width (mm) | 81 |
| Height (mm) | 42 |
| Diameter (mm) | 81 |

Sensor Information

Type of sensor No Sensor

Why Any-lamp?

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 Up to **7 years warranty**  **Easy** return process