



Specifications Philips LED Downlight
 Ledinaire DN065B Metal White 19W
 2000lm 110D - 830-840-865 CCT |
 225mm - Cutout 200mm - IP20



[View Product](#)

General Information

| | |
|--------------------------|---|
| SKU | 246866 |
| EAN | 8719514464452 |
| Brand | Philips |
| Manufacturer Name | DN065B G4 LED20/830_840_865 19W D200 RD |
| Any Lamp all-in warranty | 3 Years |
| Average Lifetime (h) | 30000 |

Technical Information

| | |
|-----------------------------|---|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 830 Warm White, 840 Cool White, 865 Daylight |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White, 6500 Daylight |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | CCT |
| Including bulb | Yes |
| Amount of bulbs required | 1 |

| | |
|--------------------------|---------------------------------------|
| Beam Angle (degree) | 110 |
| Luminous Efficacy (lm/W) | 105 |
| Power factor | >0.90 |
| Unified Glare Rating | < 28 - for hallways and storage rooms |
| Optical Cover | Plastic |
| Finish of Reflector | Frosted |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|------------------------|
| EOC8 | 46445200 |
| Mounting Method | Recessed |
| Cut out (mm) | 200 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature | -20 to +40 |
| Housing | Metal |
| Colour of the Fixture | White |
| Colour of material | White |
| Fixture Connection | Screw terminal, 2-pole |
| Series | DN065B |

Dimensions

Diameter (mm)

Why Any-lamp?

225

Sensor Information Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor

 **Easy** return process